

PRIORITY

COMPLIANCE WITH RULE 17.1(a) OR (b)





The Patent Office Concept House Cardiff Road Newport South Wales

NP10 8QQ

RECEIVED

0 5 APR 2005

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.


In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc,

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Dated

14 March 2005





Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

[EFFECTIVE COAY]

The Patent Office

Cardiff Road Newport South Wales NP10 8QQ

1. Your reference

SP62H02/P-GB HK/JR

Patent application number
 (The Patent Office will fill this part in)

1 9 MAR 2004

0406225.3

 Full name, address and postcode of the or of each applicant (undertine all surnames)

Sprog Ltd 14 Old Hall Road Gatley Cheadle

Patents ADP number (If you know ii)

Cheshire SK8 48E

If the applicant is a corporate body, give the country/state of its incorporation

England

7823206001

Title of the invention

Mattress

5. Name of your agent (if you bear one)

"Address for service" in the United Kingdom to which all correspondence should be sent (Including the pushcode)

Hammonds Rutland House 148 Edmund Street Birmingham B3 2UR

8655 62000,

Patients ADP number (if you know it)

 Priority: Complete this section if you are declaring priority from one or more earlier patent applications, filed in the last 12 months.

Country

Priority application number
(if you know it)

Date of filing (day/month/yeur)

 Divisionals, etc: Complete this section only if this application is a divisional application or resulted from an entitlement dispute (see note f)

Number of earlier UK application

Date of filing (day/month/year)

8. Is a Patents Form 7/77 (Statement of Inventorship and of right to grant of a patent) required in support of this request?

Answer YES if:

YES

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a emporate body.
   Otherwise answer NO (See nute d)

Patents Form 1/77

0098360 19-Mar-04 06:38

Latents Form 1/77

 Accompanying documents: A patent application must include a description of the invention.
 Not counting duplicates, please enter the number of pages of each item accompanying this form:

Continuation sheets of this form

THE PATENT OFFICE NA 1 9 MAR 2004

RECEIVED BY FAX

Description 6 Claim(s) 2 Claim(s)

Abstract 1

Drawing(s)

Mp

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for a preliminary examination and search (Patents Form 9/77)

Request for a substantive examination
(Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature(s)

Hammonds

Date 19.3.04

 Name, daytime telephone number and e-mail address, if any, of person to contact in the United Kingdom

Jonathan Moore 0870 839 3300 jonathan.moore@hammonds.com

#### Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

#### Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be anached to this form.
- d) If you have answered YES in part 8, a Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) Part 7 should only be completed when a divisional application is being made under section 15(4), or when an application is being made under section 8(3), 12(6) or 37(4) following an entitlement dispute. By completing part 7 you are requesting that this application takes the same filing date as an earlier UK application. If you want the new application to have the same priority date(s) as the earlier UK application, you should also complete part 6 with the priority details.

Aug 03

Patents Form 1/77

0098360 19-Mar-04 06:

Applicant: Attorney's ref.:

Sprog Ltd SP62H02/P-GB DUPLICATE

#### Mattress

The present Invention relates to bedding apparatus, and more particularly relates to mattresses with enhanced heat dissipation properties.

WO01/00064 discloses a unit for supporting a baby. The unit includes a supporting surface. The surface is shaped so that when a baby is supported on the surface, the baby's normal anatomical cervical spine curvature is maintained. The supporting surface may have first and second parts, the first part being adapted to accommodate the head, and the second part being adapted to accommodate the remainder of the body of the baby. The first and second parts may be disposed relative to one another so as to support the back of the baby's head in a position posterior to the upper part of the remainder of the baby's body. The first part may define a cavity. The supporting surface may be surrounded by a peripheral wall. The unit may be a mattress but could also be a chair.

It is well established that it is undesirable for persons to experience overheating while sleeping, and the especially so in the case of bables and small children, whether in a bed, cot, Moses basket, etc. The human body is a heat source and, when surrounded by bedding materials, will experience overheating if the heat is not allowed to dissipate.

Previously, certain techniques have been proposed that attempt to address the somewhat different problem of suffocation avoidance. US-A-5,561,879 discloses a mattress for supporting an infant in a supine position during sleep. Breathing apertures (holes) are directed through an inclined headwall of a main cushion member an through a pair of lateral guides to preclude blocking of the infant's breathing during sleep, and reduce the risk of infant sleeping death.

In-US-A-4,536,996-there is disclosed a mattress for children with a removable insert. The insert has a plurality of perforations extending from its top face to its bottom face that reduce the risk of suffocation.

However, a problem with known mattresses is that at most they are concerned with getting enough air to the person (e.g. child, baby) for unimpaired breathing. They do not provide a means of increasing or optimising the taking away of heat (embodied in warm air) from the person.

Applicant: Attorney's ref.:

Sent By: J D Reynolds;

olicant: Sprog Ltd comev's ref.: SP62H02/P-GB

There is a need for a mattress that overcomes the aforementioned problems and provides improved heat flow characteristics.

+44 1865 553735;

The present invention provides a mattress, comprising: a resilient body having at least one upper surface portion for supporting, in use, a person, and a plurality of surface channels disposed in the or each upper surface portion and extending parallel thereto.

Preferably, the body has an axis of elongation corresponding to the head-to-toe direction of the person lying, in use, on the mattress, and at least one upper surface portion is inclined relative to the axis of elongation.

Preferably, at least some of the surface channels have a component of direction parallel to the axis of elongation and in the direction of rising incline of the or each inclined surface portion.

In a preferred embodiment, at least some of the surface channels extend substantially diagonally so as to make an angle of less than 90° with the axis of elongation. The surface channels may have any transverse dimension at the surface that is sufficient to achieve effective dissipation of warm air. Suitably, by way of example, this transverse dimension is about 4 to 15 mm. The surface channels are suitably spaced apart at the surface by any distance that is suitable to accommodate the surface channels but does not adversely affect the ability of the surface to support a person. Suitably, by way of example, this spacing is about 5 to 20 mm. The surface channels may have a transverse cross-sectional area that varies along the length of the channel, for example increasing in size with proximity to the sidewalls of the resilient body. Preferably, the surface channels are distributed over substantially the entire surface area of said surface portions.

Preferably, the body-comprises sidewalls adjacent said at least one surface portion, the mattress further including at least one connecting channel, the or each connecting channel being in communication with a plurality of said surface channels and with at least one sidewall. Suitably, the or each connecting channel is disposed in the or each upper surface portion. The connecting channels may include a connecting channel extending centrally parallel to said axis of elongation, and/or include a connecting channel extending substantially transverse to said axis of elongation.

Sent By: J D Reynolds;

Applicant: Attorney's ref.: Sprog Ltd SP82H02/P-GB

In one embodiment, the upper surface portion includes a body surface portion, for supporting, in use, the body of a person, a head surface portion, for supporting, in use, the head of a person, and/or a top surface portion. In this case, a connecting channel extending substantially transverse to said axis of elongation extends along the lowermost region of said head surface portion.

An advantage of the present invention is that the surface channels in the inclined surface portions extend away from the person's body in an upwardly-rising manner. Thus, due the natural effect of warm air rising, the air warmed by the body passes along and up the surface channels and out to the atmosphere, where possible via a connecting channel. A further advantage of the invention is the possibility of reducing sudden infant death, to the extent that this is caused by overheating.

Embodiments of the present invention will now be described, by way of example, with reference to the accompanying drawings, in which:

Figure 1 is a perspective view of a mattress in accordance with one embodiment of the invention;

Figure 2 shows (a) a cross sectional view at II-II of the mattress of Fig. 1, and (b) a lateral view of the mattress of Fig. 1; and

Figure 3 illustrates a cross-section of the surface channels in a mattress accordance with another embodiment of the invention, (a) at or near the midsection, and (b) at the exterior sidewalls.

As used herein, "mattress" is taken to mean any type of resilient object for supporting a young child or baby, and which includes, among other things, mattresses for traditional beds, cots, cribs, bassinets, prams, pushchairs, or for Moses baskets, seats of various kinds, and so on. In this respect, although the invention is advantageously employed for children of various ages, it is particular beneficial for babies and children up to the age of about 3 years. At the same time, the invention would provide similar benefits to adult users when embodied in an adult-size mattress.

Figure 1 is a perspective view of a mattress in accordance with one embodiment of the invention. In this example, the mattress is designed for a very young child or baby. The mattress (generally designated 2) has a rectangular base 4 and has generally planar sidewalls 6, and top and bottom walls 8, 10 respectively. As can be seen, the mattress 2 has

) Applicant: Attorney's ref.:

Sprog Ltd SP82H02/P-GB

an axis of elongation, partially indicated at 12. Suitably, the mattress 2 is made of polymer foam, as is well known in the art in the manufacture of mattress/cushion products, and shaped using conventional injection moulding techniques

The mattress 2 comprises three sections arranged along the axis of elongation 12 — a body section 14, a head section 16 and a top section 18. Some or all of the sections 14, 16, 18 may be "scooped out" to provide a generally concave cross-section relative to the base 4, i.e. so that the thickness of the mattress 2 at the sidewalls 6 is greater than at the centreline 12: this helps to maintain the person lying on the mattress in a stable position. In use, the body section 14 supports the body of the person (e.g. baby or young child), and the head section 16 supports the head of the person.

In preferred embodiments, the general configuration of the mattress 2 is a wedge shape. Thus, the body section 14 has an upward incline as you move along the centreline 12 from the foot to the head of the person. Top section 18 may be flat or have a gentle incline in either direction. However, the head section 16 has a generally partially cylindrical cross-sectional shape (viewed transversely to the centreline 12); and the head section comprises a first part 20 and a second part 22. The first part 20 is inclined in the same direction as the body section 14, whereas the second part 22 is inclined in the opposite direction. The shape of the head section 16 beneficially enables the person's head to move freely from side to side during use, and this is facilitated by notches 23 (one of which, in use, is located generally below the neck of the person).

There is provided on the surfaces 24, 26, 28 of the section 14, 16, 18, respectively a pattern of surface channels 30. The surface channels 30 are elongate channels that may be straight or curved, and may have a U-shaped, circular, square, rectangular cross-sectional profile. Suitably, the cross-sectional dimensions of the surface channels 30 are about 4 to 15 mm in width and about 4 to 15 mm in depth. Suitably, each-surface channel 30 is separated from an adjacent surface channel on the surface by about 5 to 20 mm.

Also provided on the upper surface of the mattress 2 is a central connecting channel 32 that extends parallel to the centreline 12, and several transverse connecting channels 34, 36, 38, 40 that are generally at right angles to the centreline 12.

On each of the surfaces 24, 26, 28, the surface channels 30 have a component of direction transversely (i.e. towards the sidewalls), and they have a component of direction in the

Sent By: J D Reynolds;

Applicant: Attorney's ref.:

Sprog Ltd SP62H02/P-GB

direction of upward incline of the surface. In other words, viewed from above, the surface channels extend diagonally (e.g. at about 45° to the centreline 12; although the angle may be anything up to 90°). Indeed, the surface channels 30 may simply comprise a series of parallel channels extending at right angles to the centreline 12. Optimally, however, the surface channels 30 follow a path that provides the shortest path for warm air to the ambient atmosphere; the channels 30 may therefore follow a non-linear, curved path.

The beneficial effects during use of the mattress will be described by considering the surface 24. This is substantially covered, in use, by the person's body (not shown). Air that is adjacent the persons body is warmed by the body. Through the natural physical effect of warm air rising against the force of gravity, this warm air has to pass in an upward direction along the surface channels 30 until it reaches the ambient atmosphere. Thus, in each of the surface channels 30 covered by the person's body (to the extent that they are covered), the warm air travels in the direction of arrows A and escapes into the ambient atmosphere, either directly upwardly, or through the ends points 44, or to a connecting channel 34.

A similar effect occurs on the other surfaces 26, 28, to the extent that they are covered by the person's head, neck or body: warm air travels in the direction of arrows B, C, D and escapes into the ambient atmosphere, either directly upwardly, or through the ends points 44, or to a connecting channel 34, 36, 38, 40. The overall effect is that heat from the person's body is efficiently taken away and dissipated into the atmosphere.

The source of incoming cold air (to replace the dissipated warm air) is either along the central connecting channel 32, and/or from below the mattress 2 in the event that the mattress 2 is formed of air-permeable foam.

Figure 2(a) shows a lateral view of the mattress of Fig. 1. It illustrates the distribution of (surface channel 30) end points 44 along the upper surface of the mattress 2. Figure 2 (b) is a cross sectional view at II-II of the mattress of Fig. 1. This illustrates the junctions of the distributed surface channels 30 with the central connecting channel 32, enabling inflow of cool air and outflow of warm air.

Figure 3 illustrates a cross-section of the surface channels in a mattress in accordance with another embodiment of the invention, (a) at or near the midsection, and (b) at the exterior sidewalls. It can be seen that the cross-sectional profile of the surface channels 30 (here, substantially U-shaped) may, in certain embodiments, be of greater dimensions (Fig. 3(b))

19-Mar-04 18:43;

Page 10/15

Applicant:
Attorney's ref.:

Sprag Ltd SP62H02/P-GB

at the exterior sidewalls 6 in Fig. 1 than those (Fig. 3(a)) at the central connecting channel 32. In this way, the flow of warm air out of the surface channels 30 can be improved.

It will be appreciated by persons skilled in the art that numerous variants are possible. Although the surface channels 30 have been described herein as extending to the sidewalls 6, in certain embodiments the channels may only extend part way to, and terminate short of, the sidewalls 6.

Also, the mattress in accordance with the invention is suitable enclosed within a fabric cover (not shown). Preferably, this cover is made of an air-permeable, heat-porous, antibacterial non-woven fabric.

Attorney's ref.:

Sprog Ltd SP62H02/P-GB

#### Claims:

1. A mattress, comprising:

a resilient body having at least one upper surface portion for supporting a person; and

a plurality of surface channels disposed in the or each upper surface portion and extending parallel thereto.

- 2. The mattress of claim 1, wherein the body has an axis of elongation corresponding to the head-to-toe direction of the person lying, in use, on the mattress, and at least one upper surface portion is inclined relative to the axis of elongation.
- 3. The mattress of claim 2, wherein at least some of the surface channels have a component of direction parallel to the axis of elongation and in the direction of rising incline of the or each inclined surface portion.
- 4. The mattress of claim 1, 2 or 3, wherein at least some of the surface channels extend substantially diagonally so as to make an angle of less than 90° with the axis of elongation.
- The mattress of any of the preceding claims, wherein the body comprises sidewalls adjacent sald at least one surface portion, the mattress further including at least one connecting channel, the or each connecting channel being in communication with a plurality of said surface channels and with at least one sidewall.
- The mattress of claim 5, wherein the or each connecting channel is disposed in the or each upper surface portion.
- 7. The mattress of claim 5 or 6, wherein the or each connecting channel includes a connecting channel extending centrally parallel to said axis of elongation, and/or includes a connecting channel extending substantially transverse to said axis of elongation.
- 8. The mattress of any of the preceding claims, wherein said surface channels have a transverse dimension at the surface of about 4 to 15 mm.

Applicant: Attorney's ref,:

Sprog Ltd SP62H02/P-GB

- 9. The mattress of any of the preceding claims, wherein said surface channels spaced apart at the surface by about 5 to 20 mm.
- 10. The mattress of any of the preceding claims, wherein said surface channels have a transverse cross-sectional area that varies along the length of the channel, for example increasing in size with proximity to the sidewalls of the resilient body.
- 11. The mattress of any of the preceding claims, wherein said at least one upper surface portion includes a body surface portion for supporting, in use, the body of a person, a head surface portion for supporting, in use, the head of a person, and/or a top surface portion.
- 12. The mattress of claim 11, when dependent on claim 7, wherein the connecting channel extending substantially transverse to said axis of elongation extends along the lowermost region of said head surface portion.
- 13. The mattress of any of the preceding claims, wherein said surface channels are distributed over substantially the entire surface area of said surface portions.
- 14. A mattress substantially as hereinbefore described with reference to the accompanying drawings.

Sent By: J D Reynolds;

+44 1865 553735;

19-Mar-04 18:44;

Page 13/15...

,:2/4.55.

Applicant: Attorney's ref.:

Sprog Ltd SP62H02/P-GB

#### **Abstract**


#### **Mattress**


A mattress, comprising: a resilient body having at least one upper surface portion for supporting a person (such as a small child or baby); and a plurality of surface channels disposed in the or each upper surface portion and extending parallel thereto. The upper surface portions (for example three, including separate surface portions for supporting the head and the body) are inclined relative to the horizontal (or preferably, suitably anatomically sloped). The surface channels have a component of direction in the direction of rising slope. In consequence, warm air that has been heated by contact with the person's body, in order to rise, passes along the surface channel and out to the surrounding atmosphere. Thus, heat is dissipated away from the person's body and helps to prevent overheating.

(Fig. 1)

20

1/2





# This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

### **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

□ BLACK BORDERS
□ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
□ FADED TEXT OR DRAWING
□ BLURRED OR ILLEGIBLE TEXT OR DRAWING
□ SKEWED/SLANTED IMAGES
□ COLOR OR BLACK AND WHITE PHOTOGRAPHS
□ GRAY SCALE DOCUMENTS
□ LINES OR MARKS ON ORIGINAL DOCUMENT
□ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

## IMAGES ARE BEST AVAILABLE COPY.

☐ OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.